



SP 230 compact desktop printer specifications

With SP 230, you have quiet, compact printers that are easy to maintain and cost you less. They fit comfortably into small spaces and give you complete control of your work, from simple set up to high speed output. And with wired and wireless connectivity for easy collaboration and a user-friendly LCD interface, printing is easy.

All printers in this series feature;

- The lowest noise level in their class less than 49B(A)
- Print 30 pages per minute
- SP 230DNw offers fast, simple printing at lower costs
- SP 230SFNw is a compact 4-1 solution

SP 230DNw/ SP 230SFNw

MAIN SPECIFICATIONS

	SP 230DNw		SP 230SFNw	
GENERAL				
Warm-up time (seconds)	28			
First output speed: B/W		8.5		
(seconds)				
Continuous output speed (ppm)		30		
Memory: maximum (MB) Dimensions: W x D x H (mm)	64 356 x 360 x 183		64 410 x 399 x 319	
Weight (kg)	7.3		11.8	
Power source		220 - 240 V, 50/60 Hz		
COPIER				
Copying process		l aser bea	m scanning and electro-photographic printing	
Multiple copying	-		Up to 99 copies	
Resolution	-		1,200 x 1,200 dpi	
Enlargement/reduction	-		25 - 400%	
PRINTER				
Printing process	Dry, single component & electro-photographic printing			
Printer language	GDI			
Print resolution: maximum (dpi)	600 x 2,400 dpi equivalent			
Interface	USB 2.0, Ethernet 10 base-T/100 base-TX, Wireless LAN (IEEE 802.11b/g/n)			
Mobile printing capability	Apple AirPrint™, Mopria, Google Cloud Print			
Windows® environments	Windows® 7/8.1/10, Windows® Server 2008/2012/201	2R2/2016		
Mac OS environments	Macintosh OS X v10.11 - v10.13			
Other supported environments	Linux environment			
SCANNER				
Scanning: B/W (ipm)	-		22	
Scanning: full colour (ipm)			7	
Resolution: maximum (dpi)	-		1,200	
FAX				
Compatibility	-		G3	
Transmission speed (seconds)			2.5	
Modem speed: maximum (Kbps)	-		33.6	
PAPER HANDLING				
Recommended paper size		A4, A5, A6, B4		
Paper input: maximum (sheets)		250		
Paper output: standard (sheets)	150		120	
Paper weight (g/m²)		60 - 163		
ECOLOGY				
Power consumption: max. (kW)		Less than 1.104		
Power consumption: operation	460		440	
(kW)				
Power consumption: ready (W)	Less than 48		Less than 42	
Power consumption: sleep (W)	Less than 6		Less than 6.2	
SOFTWARE				
@Remote, Streamline NX v3, dev	vice management only (not embedded), Device Manage	r NX		
CONSUMABLES				
Startar tapar (printa)	700			

ISO9001 certified, ISO14001

certified, ISO27001 certified All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear.

Copyright © 2018 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.

≚ Rex•Rotary	1
---------------------	---

Starter toner (prints)

Toner (regular yield) (prints)

Consumable yield measuring

Toner (high yield) (prints)

method ISO/IEC 19752

Drum (sheets)

700

12,000

1,200

3,000

www.rexrotary-iberica.com





WiFi