

Declaration of yield:

Model: RICOH/Gestetner/Savin/Lanier/nashuatec/Rex-Rotary
IM 4000/ IM 4000A/ IM 4000G/ IM 5000/ IM 5000A/ IM 5000G/ IM 6000/ IM 6000G
Toner Cartridge: Print Cartridge MP 6054S

Toner cartridge yield
Average Yield of Print Cartridge MP 6054S: 47,426 standard pages.
Declared yield value in accordance with ISO/IEC 19752

90% Lower Confidence

IM 6000 44,973

Date tested : Jan 7th, 2021 to Mar 5th, 2021

For questions concerning testing contact : Ricoh Industry Co,LTD.

Number of Cartridge used in testing :	K=24
Number of Cartridge used in calculations :	K=18
Type of Cartridge :	Bottle separated from PCDU
Shake Procedure Used?	-
Print mode :	Continuous (100 pages/job), 5 minutes interval
Number of Engines used in testing :	3 units
Media Used :	Ricoh my paper 67g/m2
Paper Size :	A4
Paper feed orientation :	Long edge feed
Computer Model :	HP PROBOOK 470 G5
Driver Version :	OEM Printer Driver PCL6 Version 10.0.19041.1
Operating System :	Windows 10
Test Page Version :	ISO_IEC_19752_2004_Test_Page.prn
Power (off/on) everyday?	Yes

Cartridge testing data :

IM 6000 #4 : 4460R917004

No.	Cartridge Lot No.	Temperature (°C)		Humidity (%RH)				Cartridge Yield	Cart. Used in Calculation
		Avg.	Max.	Min.	Avg.	Max.	Min.		
1	60-0307	23.8	24.5	23.0	49.3	50.0	48.5	50235	Y
2	60-0307	23.8	24.5	23.0	49.3	50.0	48.5	49482	Y
3	60-0307	24.8	25.5	24.0	49.8	50.5	49.0	42409	Y

IM 6000#5 : 4460R917005

No.	Cartridge Lot No.	Temperature (°C)		Humidity (%RH)				Cartridge Yield	Cart. Used in Calculation
		Avg.	Max.	Min.	Avg.	Max.	Min.		
1	60-0307	23.8	24.5	23.0	49.3	50.0	48.5	51657	Y
2	60-0307	23.8	24.5	23.0	49.3	50.0	48.5	47097	Y
3	60-0307	24.8	25.5	24.0	49.8	50.5	49.0	41035	Y

IM 6000 #6 : 4460R917006

No.	Cartridge Lot No.	Temperature (°C)		Humidity (%RH)				Cartridge Yield	Cart. Used in Calculation
		Avg.	Max.	Min.	Avg.	Max.	Min.		
1	60-0307	23.8	24.5	23.0	49.3	50.0	48.5	50173	Y
2	60-0307	23.8	24.5	23.0	49.3	50.0	48.5	50663	Y
3	60-0307	24.8	25.5	24.0	49.8	50.5	49.0	44089	Y